

## ADVANCED PLACEMENT PHYSICS 2 EQUATIONS, EFFECTIVE 2015

CONSTANTS AND CONVERSION FACTORS	
Proton mass, $m_p = 1.67 \times 10^{-27}$ kg Neutron mass, $m_n = 1.67 \times 10^{-27}$ kg Electron mass, $m_e = 9.11 \times 10^{-31}$ kg Avogadro's number, $N_0 = 6.02 \times 10^{23}$ mol <sup>-1</sup> Universal gas constant, $R = 8.31$ J/(mol·K) Boltzmann's constant, $k_B = 1.38 \times 10^{-23}$ J/K	Electron charge magnitude, $e = 1.60 \times 10^{-19}$ C 1 electron volt, $1 \text{ eV} = 1.60 \times 10^{-19}$ J Speed of light, $c = 3.00 \times 10^8$ m/s Universal gravitational constant, $G = 6.67 \times 10^{-11}$ m <sup>3</sup> /kg·s <sup>2</sup> Acceleration due to gravity at Earth's surface, $g = 9.8$ m/s <sup>2</sup>
1 unified atomic mass unit, Planck's constant, Vacuum permittivity, Coulomb's law constant, $k = 1/4\pi\epsilon_0 = 9.0 \times 10^9$ N·m <sup>2</sup> /C <sup>2</sup> Vacuum permeability, Magnetic constant, $k' = \mu_0/4\pi = 1 \times 10^{-7}$ (T·m)/A 1 atmosphere pressure,	$1 \text{ u} = 1.66 \times 10^{-27}$ kg = 931 MeV/c <sup>2</sup> $h = 6.63 \times 10^{-34}$ J·s = $4.14 \times 10^{-15}$ eV·s $hc = 1.99 \times 10^{-25}$ J·m = $1.24 \times 10^3$ eV·nm $\epsilon_0 = 8.85 \times 10^{-12}$ C <sup>2</sup> /N·m <sup>2</sup> $\mu_0 = 4\pi \times 10^{-7}$ (T·m)/A $1 \text{ atm} = 1.0 \times 10^5$ N/m <sup>2</sup> = $1.0 \times 10^5$ Pa

UNIT SYMBOLS	meter, m	mole, mol	watt, W	farad, F
	kilogram, kg	hertz, Hz	coulomb, C	tesla, T
	second, s	newton, N	volt, V	degree Celsius, °C
	ampere, A	pascal, Pa	ohm, Ω	electron volt, eV
	kelvin, K	joule, J	henry, H	

PREFIXES		
Factor	Prefix	Symbol
10 <sup>12</sup>	tera	T
10 <sup>9</sup>	giga	G
10 <sup>6</sup>	mega	M
10 <sup>3</sup>	kilo	k
10 <sup>-2</sup>	centi	c
10 <sup>-3</sup>	milli	m
10 <sup>-6</sup>	micro	μ
10 <sup>-9</sup>	nano	n
10 <sup>-12</sup>	pico	p

VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLES							
$\theta$	0°	30°	37°	45°	53°	60°	90°
$\sin \theta$	0	1/2	3/5	$\sqrt{2}/2$	4/5	$\sqrt{3}/2$	1
$\cos \theta$	1	$\sqrt{3}/2$	4/5	$\sqrt{2}/2$	3/5	1/2	0
$\tan \theta$	0	$\sqrt{3}/3$	3/4	1	4/3	$\sqrt{3}$	∞

- The following conventions are used in this exam.
- I. The frame of reference of any problem is assumed to be inertial unless otherwise stated.
  - II. In all situations, positive work is defined as work done on a system.
  - III. The direction of current is conventional current: the direction in which positive charge would drift.
  - IV. Assume all batteries and meters are ideal unless otherwise stated.
  - V. Assume edge effects for the electric field of a parallel plate capacitor unless otherwise stated.
  - VI. For any isolated electrically charged object, the electric potential is defined as zero at infinite distance from the charged object.

**ADVANCED PLACEMENT PHYSICS 2 EQUATIONS, EFFECTIVE 2015**

**MECHANICS**

$v_x = v_{x0} + a_x t$	$a = \text{acceleration}$
$x = x_0 + v_{x0} t + \frac{1}{2} a_x t^2$	$A = \text{amplitude}$
$v_x^2 = v_{x0}^2 + 2a_x(x - x_0)$	$d = \text{distance}$
$\vec{a} = \frac{\sum \vec{F}}{m} = \frac{\vec{F}_{net}}{m}$	$E = \text{energy}$
$ \vec{F}_f  \leq \mu  \vec{F}_n $	$F = \text{force}$
$a_c = \frac{v^2}{r}$	$f = \text{frequency}$
$\vec{p} = m\vec{v}$	$I = \text{rotational inertia}$
$\Delta\vec{p} = \vec{F} \Delta t$	$K = \text{kinetic energy}$
$K = \frac{1}{2} m v^2$	$k = \text{spring constant}$
$\Delta E = W = F_{\parallel} d = F d \cos \theta$	$L = \text{angular momentum}$
$P = \frac{\Delta E}{\Delta t}$	$\ell = \text{length}$
$\theta = \theta_0 + \omega_0 t + \frac{1}{2} \alpha t^2$	$m = \text{mass}$
$\omega = \omega_0 + \alpha t$	$P = \text{power}$
$x = A \cos(\omega t) = A \cos(2\pi f t)$	$p = \text{momentum}$
$x_{cm} = \frac{\sum m_i x_i}{\sum m_i}$	$r = \text{radius or separation}$
$\vec{\alpha} = \frac{\sum \vec{\tau}}{I} = \frac{\vec{\tau}_{net}}{I}$	$T = \text{period}$
$\tau = r_{\perp} F = r F \sin \theta$	$t = \text{time}$
$L = I \omega$	$U = \text{potential energy}$
$\Delta L = \tau \Delta t$	$v = \text{speed}$
$K = \frac{1}{2} I \omega^2$	$W = \text{work done on a system}$
$ \vec{F}_s  = k  \vec{x} $	$x = \text{position}$
	$y = \text{height}$
	$\alpha = \text{angular acceleration}$
	$\mu = \text{coefficient of friction}$
	$\theta = \text{angle}$
	$\tau = \text{torque}$
	$\omega = \text{angular speed}$
	$U_s = \frac{1}{2} k x^2$
	$\Delta U_g = m g \Delta y$
	$T = \frac{2\pi}{\omega} = \frac{1}{f}$
	$T_s = 2\pi \sqrt{\frac{m}{k}}$
	$T_p = 2\pi \sqrt{\frac{\ell}{g}}$
	$ \vec{F}_g  = G \frac{m_1 m_2}{r^2}$
	$\vec{g} = \frac{\vec{F}_g}{m}$
	$U_G = -\frac{G m_1 m_2}{r}$

**ELECTRICITY AND MAGNETISM**

$ \vec{F}_E  = \frac{1}{4\pi\epsilon_0} \frac{ q_1 q_2 }{r^2}$	$A = \text{area}$
$\vec{E} = \frac{\vec{F}_E}{q}$	$B = \text{magnetic field}$
$ \vec{E}  = \frac{1}{4\pi\epsilon_0} \frac{ q }{r^2}$	$C = \text{capacitance}$
$\Delta U_E = q \Delta V$	$d = \text{distance}$
$V = \frac{1}{4\pi\epsilon_0} \frac{q}{r}$	$E = \text{electric field}$
$ \vec{E}  = \left  \frac{\Delta V}{\Delta r} \right $	$\mathcal{E} = \text{emf}$
$\Delta V = \frac{Q}{C}$	$F = \text{force}$
$C = \kappa \epsilon_0 \frac{A}{d}$	$I = \text{current}$
$E = \frac{Q}{\epsilon_0 A}$	$\ell = \text{length}$
$U_C = \frac{1}{2} Q \Delta V = \frac{1}{2} C (\Delta V)^2$	$P = \text{power}$
$I = \frac{\Delta Q}{\Delta t}$	$Q = \text{charge}$
$R = \frac{\rho \ell}{A}$	$q = \text{point charge}$
$P = I \Delta V$	$R = \text{resistance}$
$I = \frac{\Delta V}{R}$	$r = \text{separation}$
$R_s = \sum_i R_i$	$t = \text{time}$
$\frac{1}{R_p} = \sum_i \frac{1}{R_i}$	$U = \text{potential (stored)}$
$C_p = \sum_i C_i$	$\text{energy}$
$\frac{1}{C_s} = \sum_i \frac{1}{C_i}$	$V = \text{electric potential}$
$B = \frac{\mu_0 I}{2\pi r}$	$v = \text{speed}$
	$\kappa = \text{dielectric constant}$
	$\rho = \text{resistivity}$
	$\theta = \text{angle}$
	$\Phi = \text{flux}$
	$\vec{F}_M = q\vec{v} \times \vec{B}$
	$ \vec{F}_M  =  q\vec{v}   \sin \theta   \vec{B} $
	$\vec{F}_M = I\vec{\ell} \times \vec{B}$
	$ \vec{F}_M  =  I\vec{\ell}   \sin \theta   \vec{B} $
	$\Phi_B = \vec{B} \cdot \vec{A}$
	$\Phi_B =  \vec{B}  \cos \theta  \vec{A} $
	$\mathcal{E} = -\frac{\Delta \Phi_B}{\Delta t}$
	$\mathcal{E} = B \ell v$

## ADVANCED PLACEMENT PHYSICS 2 EQUATIONS, EFFECTIVE 2015

FLUID MECHANICS AND THERMAL PHYSICS	WAVES AND OPTICS
$\rho = \frac{m}{V}$ $P = \frac{F}{A}$ $P = P_0 + \rho gh$ $F_b = \rho Vg$ $A_1 v_1 = A_2 v_2$ $P_1 + \rho gy_1 + \frac{1}{2} \rho v_1^2 = P_2 + \rho gy_2 + \frac{1}{2} \rho v_2^2$ $\frac{Q}{\Delta t} = \frac{kA \Delta T}{L}$ $PV = nRT = Nk_B T$ $K = \frac{3}{2} k_B T$ $W = -P \Delta V$ $\Delta U = Q + W$	$\lambda = \frac{v}{f}$ $n = \frac{c}{v}$ $n_1 \sin \theta_1 = n_2 \sin \theta_2$ $\frac{1}{s_i} + \frac{1}{s_o} = \frac{1}{f}$ $ M  = \left  \frac{h_i}{h_o} \right  = \left  \frac{s_i}{s_o} \right $ $\Delta L = m\lambda$ $d \sin \theta = m\lambda$
<p><i>A</i> = area  <i>F</i> = force  <i>h</i> = depth  <i>k</i> = thermal conductivity  <i>K</i> = kinetic energy  <i>L</i> = thickness  <i>m</i> = mass  <i>n</i> = number of moles  <i>N</i> = number of molecules  <i>P</i> = pressure  <i>Q</i> = energy transferred to a system by heating  <i>T</i> = temperature  <i>t</i> = time  <i>U</i> = internal energy  <i>V</i> = volume  <i>v</i> = speed  <i>W</i> = work done on a system  <i>y</i> = height  <i>ρ</i> = density</p>	<p><i>d</i> = separation  <i>f</i> = frequency or focal length  <i>h</i> = height  <i>L</i> = distance  <i>M</i> = magnification  <i>m</i> = an integer  <i>n</i> = index of refraction  <i>s</i> = distance  <i>v</i> = speed  <i>λ</i> = wavelength  <i>θ</i> = angle</p>
<b>MODERN PHYSICS</b>	<b>GEOMETRY AND TRIGONOMETRY</b>
$E = hf$ $K_{\max} = hf - \phi$ $\lambda = \frac{h}{p}$ $E = mc^2$	<p>Rectangle  <i>A</i> = <i>bh</i></p> <p>Triangle  <math>A = \frac{1}{2}bh</math></p> <p>Circle  <math>A = \pi r^2</math>  <math>C = 2\pi r</math></p> <p>Rectangular solid  <math>V = \ell wh</math></p> <p>Cylinder  <math>V = \pi r^2 \ell</math>  <math>S = 2\pi r \ell + 2\pi r^2</math></p> <p>Sphere  <math>V = \frac{4}{3} \pi r^3</math>  <math>S = 4\pi r^2</math></p>
<p><i>E</i> = energy  <i>f</i> = frequency  <i>K</i> = kinetic energy  <i>m</i> = mass  <i>p</i> = momentum  <i>λ</i> = wavelength  <i>φ</i> = work function</p>	<p><i>A</i> = area  <i>C</i> = circumference  <i>V</i> = volume  <i>S</i> = surface area  <i>b</i> = base  <i>h</i> = height  <i>ℓ</i> = length  <i>w</i> = width  <i>r</i> = radius</p> <p>Right triangle  <math>c^2 = a^2 + b^2</math>  <math>\sin \theta = \frac{a}{c}</math>  <math>\cos \theta = \frac{b}{c}</math>  <math>\tan \theta = \frac{a}{b}</math></p> 